

# MS0408-A

## ELECTRIC SELF-PROPELLED MINI SCISSOR LIFT

# HELI

### Product Highlights

#### High performance

- ★Lightweight and heavy load
- ★Compact design of the entire machine, flexible movement, and the ability to enter elevators

#### Convenient maintenance

- ★Exclusive open chassis design makes equipment clean and maintenance more convenient
- ★Drawer style door design for more convenient maintenance
- ★High universality of components and no pressure on spare parts



### Standard Features



Drivable at full height	Proportional controls	Foldable guardrails
Automatic brake system	Non-marking tires	Emergency stop button
Explosion-proof oil tubes	Emergency lowering button	Tilt alarm
Buzzer	Diagnosis system	Automatic pothole protection
Safety Support bar	Flash light	Maintenance free battery
Forklift pockets and lifting holes	AC power to platform	Hydraulic drive
Self lock gate on platform	Extended Platform	

### Options Features

Overload sensor	Power socket to platform	Top Stop Sensor
Working Light	GPS	Electric drive

Model	MS0408-A
Dimension	
Max. Working Height	6.4m
A Max. Platform Height	4.4m
B Max. Outreach	0.55m
C Length Stowed	1.5m
Length - Platform Extension	1.8m
D Width Stowed	0.76m
E Height Stowed (guardrails unfolded)	2.04m
Height Stowed (guardrails folded)	1.72m
F Wheelbase	1.075m
Ground Clearance	0.06m
Pothole protection board ground Clearance(down)	0.015m
Platform Size(L×W×H)	1.29m×0.76m×1.1m
Skirting Board Height	0.17m
Performance	
Max. Load number (indoor)	2pers
Lifting Capacity	240kg
Lifting Capacity (extended platform)	100kg
Drive Speed (Stowed)	3km/h
Drive Speed (Raised)	0.7km/h
Rising Time	23s
Lowering Time	19s
Gradeability	25%
Turing Radius - inside	0.35m
Tilt Sensor - Front to Back	3°
Tilt Sensor - Side to Side	1.5°
Tire Specification/ Type	Non-marking solid Tyres 230mm
Power	
Drive Mode	Electric drive,2WD×2WS
Power Unit Motor (voltage/power)	24V/0.8kw
Hydraulic Tank Capacity	2L
Battery Specifications	114Ah
Control Voltage	24V
Charger (Input Voltage/Output Current)	96-265V/15A
Weight	
Weight	920kg
Standard	GB/CE

MS0408-A



MS0408-A

