

ZOOMLION

CRAWLER SCISSOR LIFTS

ZS2242C/ZS1532C

Comply with CE Standard

HIGHLIGHTS

High Performance

- ▶ Rubber crawler provides small ground pressure and great obstacle crossing ability
- ▶ Pivot steering with good maneuverability
- ▶ Simple single handle control for steering and walking
- ▶ Work height of 8.8m with high working efficiency (ZS2242C only)

Cost Effectiveness

- ▶ Knuckles lubrication-free and maintenance-free
- ▶ AC motor full lifecycle maintenance-free

FEATURES

Standard Features

Proportional controls	Over tilt protective system
All motion alarm	Drivable at full height
Fold-down handrails	Hour meter
Flashing beacon	Extension deck (unidirectional)
Self-closing entry gate	Charging protection system
Autobrake system	Scissor maintenance prop
Emergency descent system	Forklift pockets
Emergency stop button	Load sensing system
On-board diagnostic	AC power to platform
Horn	

Accessories & Options

- ▶ Platform work lights
- ▶ Air line to platform
- ▶ Overhead protection bar



ACCESS WITH ZOOMLION GREEN

Phone: 0086(731)-88353680 0086(731)-88250971
E-mail: awm@zoomlion.com

Add: ZOOMLION Wangcheng Industrial Park, Tengfei Road 997, Changsha, Hunan, China
Web: www.en.zoomlion.com

CRAWLER SCSSIOR LIFTS

ZS2242C/ZS1532C

Comply with CE Standard

Model	ZS2242C		ZS1532C	
	Imperial	Metric	Imperial	Metric
Size				
Work Height	28ft11in	8.80m	21ft 4in	6.5m
A Platform Height-Elevated	22ft4in	6.80m	14ft 9in	4.5m
B Platform Height-Stowed	3ft 8in	1.12m	3ft 3in	0.99m
C Platform Length	6ft4in	1.94m	4ft 3in	1.29m
D Platform Width	3ft1in	0.95m	2ft 4in	0.7m
Platform Extension	3ft	0.91m	2ft	0.6m
E Overall Height (Rails Up)	7ft5in	2.26m	6ft 11in	2.1m
Overall Height (Rails Down)	5ft10in	1.77m	5ft 9in	1.74m
F Overall Length	6ft11in	2.1m	4ft 9in	1.46m
G Overall Width	3ft5in	1.05m	2ft 8in	0.81m
H Ground Clearance	4.5in	0.127m	3in	0.07m
Performance				
Platform Capacity	550lb	250kg	530lb	240kg
Capacity on Deck Extension	250l	113kg	220lb	100kg
Max. Number of Workers	2		1	
Drive Speed (Stowed)	1.25mph	2km/h	1.25mph	2km/h
Drive Speed (Raised)	0mph	0km/h	0mph	0km/h
Turning Radius	0in	0m	0in	0m
Drive Motor	24V/2×1.8KW		24V/2×0.77kW	
Up/Down Time	34s/30s		23s/25s	
Gradeability	30%(17°)		25%(14°)	
Max. Working Slope (Lateral/Vertical)	2°/2°		1.7°/1.7°	
Drive	Rear Wheels		Rear Wheels	
Brake	Rear Wheels		Rear Wheels	
Power				
Battery	4×6V/220Ah		4×12V/115Ah	
Charger	24V/30A		24V/30A	
Weight				
Gross	3750lb	1700kg	1975lb	895kg

